



NOTE: 1) HYDRO @ 165 PSIG. MIN.

| | | | |
|--------------------|-----------------------|---------------------------------|-------------------|
| SHELL / HEADS | .200" SA-455 2:1 S.E. | 48-VG-1060-R | REV. 8-22-07 |
| | JOGGLE | | DATE: 4-13-99 |
| | | FOR: HANSON STANDARD | |
| | | VERT. AIR TANK | |
| | .200" SA-455 | | |
| | | INSIDE: UNPAINTED | |
| | | OUTSIDE: PRIME | |
| | | CAD "B" SIZE UNDER "STD"-SERIES | |
| | | BY: J.G. | SCALE: 1/2" = 12" |
| | | ROY E. HANSON JR. MFG. | |
| | | 1600 E. WASHINGTON BLVD. | |
| | | LOS ANGELES, CA 90021 | |
| M.A.W.P. | 125 PSIG. @ 400 °F | | |
| M.D.M.T. | -20 °F @ 125 PSIG. | | |
| ASME. SECTION VIII | DIV. 1, 2004 ADD 2006 | | |
| X-RAY: | RT-4 SPOT L.S. ONLY | | |
| GALLONS: | 1060 | WT. 1589 | LBS. |
| SERIAL NO. | | | |
| N.B. | | | |