



NOTE: 1) HYDRO @ 163 PSIG. MIN.

| SHELL / HEADS | | REV. |
|-------------------------------------|----------------------------|---------------|
| M.A.W.P. | 125 PSIG. @ 400 °F | 12-10-02 |
| M.D.M.T. | -20 °F | DATE: 6-15-99 |
| ASME SECTION VIII | DIV. 1, 2001 ADD 2002 | |
| X-RAY: | RT-4 SPOT L.S. & HDS. G.S. | |
| GALLONS: | 5000 | |
| SERIAL NO. | WT. 6033 LBS. | |
| N.B. | | |
| .3125" SA-455 2:1 S.E. (.244" MIN.) | | |
| TOP - .288" SA-455 @ 97" | | |
| BTM. - .337" SA-455 @ 84 1/4" | | |
| FOR: HANSON STANDARD | | |
| VERT. AIR TANK | | |
| INSIDE: UNPAINTED | | |
| OUTSIDE: PRIME | | |
| CAD "B" SIZE UNDER "STD"-SERIES | | |
| BY: J.G. SCALE: 3/8"=12" | | |
| ROY E. HANSON JR. MFG. | | |
| 1924 COMPTON AVE. | | |
| LOS ANGELES, CA 90011 | | |