



GUARD & VALVE LAYOUT PER: SK-7499-B-2B

OTHER	CALIF.	LIQUID LEVEL	"A"	D.T. ON N.P.L.
79.8%	86 1/2%			
31 1/2"	17"			
42.9"	28.4"			

NOTE: 1) HYDRO @ 327 PSIG. MIN.  
 2) INTERNAL PIPES PER: PA-412-B-1B

SHELL / HEADS	OTHER
.246" MIN. SA-455 2:1 S.E.	
JOGGLE (.289" OFFSET)	
BLUE STRIPE	
.289" SA-455 - TOP	
.3125" SA-455 - LOWER	
M.A.W.P. 250 PSIG. @ 200 °F	
M.D.M.T. -20 °F @ 250 PSIG.	
ASME. SECTION VIII DIV. 1, 2004 ADD 2005	
X-RAY: RT-4 SPOT L.S. & HDS. G.S.	
GALLONS: 1150	WT. 2906 LBS.
SERIAL NO.	
N.B.	

PA-412-B		REV. 4-24-06
		DATE: 4-17-86
FOR: HANSON STANDARD		
VERT. L.P.G. TANK		
SURFACE AREA = 194.1 SQ. FT.		
C.F.M. REQ'D 4033		
INSIDE: UNPAINTED & DEHYDRATE		
OUTSIDE: PRIME		
LEG ZONE: 4-15 KM.		
BY: E.S.	SCALE: 1/2" = 12"	
<b>ROY E. HANSON JR. MFG.</b>		
1924 COMPTON AVE. LOS ANGELES, CA 90011		