



OTHER	CALIF.
LIQUID LEVEL	86 1/2%
"A"	10"
D.T.	21 1/4" 13 3/8"

NOTE: 1) HYDRO @ 325 PSIG. MIN.  
2) INTERNAL PIPES PER: PA-720-B

SHELL / HEADS	.210" SA-455 2:1 S.E.
	JOGGLE
	.250" SA-455
M.A.W.P.	250 PSIG. @ 200 °F
M.D.M.T.	-20 °F @ 250 PSIG.
ASME. SECTION VIII	DIV. 1, 2001 ADD 2002
X-RAY:	RT-4 SPOT L.S. & HDS. G.S.
GALLONS:	499
WT.	1202 LBS.
SERIAL NO.	
N.B.	

<b>PA-414-B</b>	REV. 2-14-03
	DATE: 3-23-99
FOR: HANSON STANDARD	
VERT. L.P.G. TANK	
SURFACE AREA = 100.1 SQ. FT.	
C.F.M. REQ'D = 2344	
INSIDE: UNPAINTED & DEHYDRATE	
OUTSIDE: PRIME	
LEG ZONE: 4-15 KM.	
BY: J.G.	SCALE: 3/4" = 12"
<b>ROY E. HANSON JR. MFG.</b>	
1924 COMPTON AVE. LOS ANGELES, CA 90011	